

522,191

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



Rec'd PCT/PTO

25 JAN 2005




(43) International Publication Date
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number
WO 2004/029343 A1

- (51) International Patent Classification⁷: **D02G 03/36**
- (21) International Application Number:
PCT/US2002/030394
- (22) International Filing Date:
25 September 2002 (25.09.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Five Farm Springs Road, Farmington, CT 06032 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **O'DONNELL, Hugh, James** [US/US]; 289 Converse Street, Longmeadow, MA 01106 (US).
- (74) Agents: **GASKEY, David, J. et al.**; Carlson, Gaskey & Olds, P.C., 400 West Maple Road, Suite 350, Birmingham, MI 48009 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELEVATOR BELT ASSEMBLY WITH PRESTRETCHED SYNTHETIC CORDS



(57) Abstract: An elevator load bearing assembly (40) includes a plurality of synthetic or polymer cords (42) within a urethane jacket (44). The cords are prestretched and the jacket prevents the stretched cords from relaxing. The inventive arrangement provides a load bearing assembly (40) that has little or no elastic or construction stretch.

WO 2004/029343 A1